Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-0585

Cross Section	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Direct	on:
Right-hand 1st	end
Inside Diamet	er:
0.212 inches	
Tempurature	Rating:
-65.0 degrees t	ahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diam	eter:
0.390 inches	
Minimum Insie	de Bending Radius:
1.500 inches	
Connection St	yle:
Swivel nut, fla	eless 1st end
End Connection	on Design:
Straight 1st en	ł
Connection Ty	/pe:
Threaded inter	nal tube 1st end
Features Prov	ided:
Nuts drilled for	lockwire
Burst Test Pre	ssure:
12000.0 pound	s per square inch
Layer Compos	sition And Location:
Outer layer bra	ided corrosion resistant steel wire
Maximum Ope	erating Pressure:
3000.0 pounds	per square inch
Thread Size:	
0.438 inches 1	st end
Hydrostatic To	est Pressure:
6000.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Me	thod And Length:
11.250 inches	working
Thread Series	Designator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measu	re:

NSN 4720-01-040-0585

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

