Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-0589

| Cross Sec | ctional Shape: |
|-------------|---|
| Round | |
| Thread Cl | ass: |
| 3b 1st end | I |
| Thread Di | rection: |
| Right-hand | d 1st end |
| Inside Dia | |
| 0.298 inch | es |
| Tempurat | ure Rating: |
| -65.0 degr | ees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside D | Diameter: |
| 0.475 inch | es |
| Minimum | Inside Bending Radius: |
| 2.500 inch | |
| Connectio | on Style: |
| Swivel nut | , flareless 1st end |
| End Conn | ection Design: |
| Straight 1s | st end |
| Connectio | on Type: |
| Threaded | internal tube 1st end |
| Features | Provided: |
| Nuts drille | d for lockwire |
| Burst Tes | t Pressure: |
| 10500.0 p | ounds per square inch |
| Layer Cor | nposition And Location: |
| Outer laye | r braided corrosion resistant steel wire |
| Maximum | Operating Pressure: |
| 3000.0 po | unds per square inch |
| Thread Si | ze: |
| 0.562 inch | es 1st end |
| Hydrostat | ic Test Pressure: |
| 6000.0 po | unds per square inch |
| Inside Su | rface Condition: |
| Smooth | |
| Measuring | g Method And Length: |
| 43.500 inc | hes working |
| Thread Se | eries Designator: |
| Unjf 1st er | nd |
| Shelf Life | : |
| N/a | |
| Unit Of M | easure: |
| | |

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

