

View Online at <https://aerobasegroup.com/nsn/4720-01-040-0590>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 190.0 degrees fahrenheit single response

Flange Thickness:

0.359 inches 1st end

Minimum Inside Bending Radius:

4.500 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

Center To Center Distance Between Bolt Holes Along Width:

1.812 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.812 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

2.375 inches 1st end

Flange Width:

2.375 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.266 inches 1st end

Raised Face Diameter:

2.135 inches 1st end

End Flange Construction:

Split 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Raised face flange 1st end

Burst Test Pressure:

600.0 pounds per square inch

Layer Composition And Location:

1st layer polytetrafluoroethylene impregnated glass fiber and 2nd layer molded polytetrafluoroethylene and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

300.0 pounds per square inch

Hydrostatic Test Pressure:

450.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.750 inches working

Flange Style:

Rectangular (includes square) 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0