Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-1857

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.391 inches	
Tempurature Rating:	
65.0 degrees fahrenheit singl	e response and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.605 inches	
Minimum Inside Bending Ra	dius:
2.880 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	t
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
10500.0 pounds per square in	ch
Layer Composition And Loc	ation:
Outer layer braided corrosion	resistant steel wire
Maximum Operating Pressu	re:
3000.0 pounds per square inc	h
Thread Size:	
0.750 inches 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inc	h
Inside Surface Condition:	
Smooth	
Measuring Method And Leng	gth:
24.625 inches working	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-01-040-1857

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

