Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-040-3515

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.195 inches |
| Tempurature Rating: |
| -20.0 degrees fahrenheit single response and 165.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.440 inches |
| Minimum Inside Bending Radius: |
| 1.000 inches |
| Exterior Color: |
| Brown or orange |
| Connection Style: |
| Swivel nut, flareless 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Internal support |
| Burst Test Pressure: |
| 500.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided polyamide cord |
| Maximum Operating Pressure: |
| 125.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 12.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 13.000 inches working |
| Thread Series Designator: |
| Unjf 1st end |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

81205-bach30bc manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0