NSN 4720-01-040-9114



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-040-9114 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees celsius and 121.0 degrees celsius single response **Quick Disconnect Size:** 0.750 inches 2nd end **Connection Style:** Push (internal) 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external boss 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer molded rubber, ethylene propylene and 2nd layer braided synthetic cord and 3rd layer braided synthetic cord and outer layer braided synthetic cord **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.750 inches 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 52.000 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4720-01-040-9114

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0