Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-0032

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single resp	ponse and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.390 inches	
Minimum Inside Bending Radius:	:
1.500 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location	1:
Outer layer braided corrosion resist	ant steel wire
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.4375 inches 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
11.125 inches working	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

