

View Online at <https://aerobasegroup.com/nsn/4720-01-041-1102>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.602 inches and 0.648 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response

Outside Diameter:

Between 0.843 inches and 0.906 inches

Minimum Inside Bending Radius:

6.000 inches

Burst Test Pressure:

700.0 pounds per square inch single response

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

150.0 pounds per square inch single response

Hydrostatic Test Pressure:

250.0 pounds per square inch single response

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and abrasion resistant

Criticality Code Justification:

Crxx

Inside Surface Condition:

Smooth

Measuring Method And Length:

4.500 inches and 4.545 inches

Material:

Rubber synthetic tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-mil-h-5593 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541z0

Mil-std (military Standard):

Mil-h-5593 spec.