Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-2147

_	
Cross Sectional S	hape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.391 inches	
Tempurature Ratii	ıg:
-65.0 degrees fahre	enheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.605 inches	
Minimum Inside B	ending Radius:
2.880 inches	
Connection Style:	
Swivel nut, flareles	s 1st end
End Connection D	vesign:
Straight 1st end	
Connection Type:	
Threaded internal to	ube 1st end
Features Provided	l:
Nuts drilled for lock	wire
Burst Test Pressu	re:
10500.0 pounds pe	r square inch
Layer Compositio	n And Location:
Outer layer braided	corrosion resistant steel wire
Maximum Operati	ng Pressure:
3000.0 pounds per	square inch
Thread Size:	
0.750 inches 1st er	ıd
Hydrostatic Test F	Pressure:
6000.0 pounds per	square inch
Inside Surface Co	ndition:
Smooth	
Measuring Method	And Length:
37.125 inches wor	king
Thread Series Des	signator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 4720-01-041-2147

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

