Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-4142

Cross Sectional SI	ape.
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.301 inches	
Tempurature Ratin	
	heit and 450.0 degrees fahrenheit single response
Outside Diameter:	
0.624 inches	
Minimum Inside Bo	nding Radius:
4.000 inches	
Connection Style:	
Swivel nut flare 2nd	end
End Connection D	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Burst Test Pressu	e:
9000.0 pounds per	quare inch
Layer Composition	And Location:
Outer layer braided	corrosion resistant steel wire
Maximum Operatir	g Pressure:
1500.0 pounds per	quare inch
Thread Size:	
0.562 inches 2nd er	d
Seat Angle:	
37.0 degrees 2nd e	d
Flow Angle:	
90.0 degrees 2nd e	d
Inside Surface Cor	dition:
Smooth	
Measuring Method	And Length:
21.875 inches work	ing
Supplementary Fe	itures:
This item has been	eviewed for asbestos material. The current approved sources, 07482, 78570, have indicated their part numbers
contained asbestos	They continue to manufacture the same part number without asbestos material
Thread Series Des	gnator:
Unjf 1st end	
Shelf Life:	
N/a	

NSN 4720-01-041-4142

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0