NSN 4720-01-041-4142

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-4142

view Offiline at https://aerobasegroup.com/hsi//4/20-01-041-4142
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.301 inches
Tempurature Rating:
-45.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
0.624 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.875 inches working
Supplementary Features:
This item has been reviewed for asbestos material. The current approved sources, 07482, 78570, have indicated their part numbers
contained asbestos. They continue to manufacture the same part number without asbestos material
Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

NSN 4720-01-041-4142

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0