NSN 4720-01-041-5535

Cross Sectional Shape:

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-5535

Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.298 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.475 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
10500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.375 inches working
Thread Series Designator:
Unjf 2nd end
Shelf Life:

NSN 4720-01-041-5535

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0