Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-5538

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.390 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Flow Angle:	
45.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
11.375 inches working	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0