Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-041-7197

	ine at https://aerobasegroup.com/hsr/4720-01-041-7137
Cross Se	ectional Shape:
Round	
Thread D	Direction:
Right-har	nd 1st end
Inside Di	ameter:
0.375 incl	hes
Tempura	iture Rating:
-40.0 deg	rees fahrenheit and 212.0 degrees fahrenheit single response
Outside	Diameter:
0.625 incl	hes
Exterior	Color:
Black	
Connecti	ion Style:
Plain 1st	end
End Con	nection Design:
Straight 1	st end
Connecti	ion Type:
Threaded	d external pipe 1st end
Burst Te	st Pressure:
900.0 pot	unds per square inch
Layer Co	omposition And Location:
1st layer	braided cotton cord and outer layer molded rubber, synthetic
Maximun	n Operating Pressure:
225.0 pou	unds per square inch
Thread S)ize:
0.250 inc	hes 1st end
Hydrosta	atic Test Pressure:
450.0 pou	unds per square inch
Outer Co	overing Environmental Protection:
Fuel resis	stant and oil resistant and mildew resistant and water resistant
Inside Su	urface Condition:
Smooth	
Measurir	ng Method And Length:
46.000 in	ches working
Media Fo	or Which Designed:
Fuel/oil,	hydrocarbon single response
Thread S	Series Designator:
Nptf 1st e	and
Shelf Life	e:
N/a	
Unit Of M	leasure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

