

View Online at <https://aerobasegroup.com/nsn/4720-01-041-7985>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.350 inches

Temperature Rating:

-350.0 degrees fahrenheit and 1200.0 degrees fahrenheit single response

Outside Diameter:

0.600 inches

Minimum Inside Bending Radius:

5.500 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal hose 1st end

Features Provided:

Nuts drilled for lockwire and identical ends

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

2700.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

900.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Hydrostatic Test Pressure:

1350.0 pounds per square inch

Outer Covering Environmental Protection:

Alcohol resistant and corrosion resistant and fuel resistant and oil resistant and water resistant

Measuring Method And Length:

7.875 inches

Special Features:

Metal band for identification

Thread Series Designator:

Nh 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0