

View Online at <https://aerobasegroup.com/nsn/4720-01-041-8961>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.150 inches and 0.230 inches

Temperature Rating:

28.0 degrees fahrenheit single response and 165.0 degrees fahrenheit single response

Outside Diameter:

0.410 inches

Minimum Inside Bending Radius:

3.000 inches

Unable To Decode:

Unable to decode or unable to decode

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded polyurethane err-100 or outer layer moulded ethylcellulose err-100

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.750 inches working and 18.750 inches working

Second End Swivel Action Capability:

Included

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene or plastic, polyamide

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0