Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-042-0235

Cross Sectional S	ane.		
Round	αμε.		
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end Inside Diameter:			
	and 0.202 inches		
Between 0.183 inch	es and 0.203 inches		
Outside Diameter:			
Between 0.311 inch			
Minimum Inside Be	nding Radius:		
2.000 inches			
Connection Style:			
Swivel nut flare 1st			
End Connection D	esign:		
Straight 2nd end			
Connection Type:			
Threaded internal tu			
Burst Test Pressur			
12000.0 pounds per			
Layer Compositior			
-	corrosion resistant steel wire		
Maximum Operatir			
3000.0 pounds per s	quare inch		
Thread Size:			
0.437 inches 1st en	1		
Seat Angle:			
37.0 degrees 1st en	t		
Hydrostatic Test P	essure:		
6000.0 pounds per s	quare inch		
Inside Surface Cor	dition:		
Smooth			
Measuring Method	And Length:		
11.380 inches			
Thread Series Des	gnator:		
Unf 1st end			
Shelf Life:			
N/a			
Unit Of Measure:			
Demilitarization:			
No			

NSN 4720-01-042-0235

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

