Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-042-1310

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.298 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.475 inches	
Minimum Inside Bending Radius:	
2.500 inches	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire	
Burst Test Pressure:	
10500.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire and outer layer spirally wrapped polyamide fab	oric
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.562 inches 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
30.500 inches working	
Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0