Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-042-2968

Cross Sectiona	Il Shape:
Round	
Thread Class:	
3b 1st end	
Thread Direction	n:
Right-hand 1st e	and
Inside Diamete	r:
0.485 inches	
Tempurature R	ating:
-65.0 degrees fa	hrenheit single response and 400.0 degrees fahrenheit single response
Outside Diame	ter:
0.720 inches	
Minimum Inside	e Bending Radius:
3.250 inches	
Connection Sty	rle:
Swivel nut, flare	eless 1st end
End Connectio	n Design:
Straight 1st end	
Connection Ty	be:
Threaded intern	al tube 1st end
Features Provid	Jed:
Nuts drilled for lo	ockwire
Burst Test Pres	ssure:
9000.0 pounds p	ber square inch
Layer Composi	tion And Location:
Outer layer braid	ded corrosion resistant steel wire
Maximum Oper	ating Pressure:
3000.0 pounds p	per square inch
Thread Size:	
0.875 inches 1st	a end
Hydrostatic Te	st Pressure:
6000.0 pounds p	per square inch
Inside Surface	Condition:
Smooth	
Measuring Met	hod And Length:
14.000 inches v	vorking
Thread Series I	Designator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measur	e:

NSN 4720-01-042-2968

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

