

View Online at <https://aerobasegroup.com/nsn/4720-01-043-0767>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.212 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.500 inches

**Minimum Inside Bending Radius:**

1.500 inches

**Angle Between Rigid Elbow Fittings In Deg:**

345.0

**Connection Style:**

Flared 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded external tube 2nd end

**Features Provided:**

Nuts drilled for lockwire

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

45.0 degrees 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.875 inches working

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0