Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-043-1533

Cross Sectional Sha	ipe:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.391 inches	
Tempurature Rating	:
-65.0 degrees fahrenł	neit single response and 400.0 degrees fahrenheit single response
Outside Diameter:	
0.605 inches	
Minimum Inside Ber	iding Radius:
2.880 inches	
Connection Style:	
Swivel nut, flareless	2nd end
End Connection Des	sign:
Elbow 2nd end	
Connection Type:	
Threaded internal tub	e 1st end
Features Provided:	
Nuts drilled for lockwi	re
Burst Test Pressure	:
10500.0 pounds per s	quare inch
Layer Composition	And Location:
Outer layer braided co	prrosion resistant steel wire
Maximum Operating	Pressure:
3000.0 pounds per so	juare inch
Thread Size:	
0.750 inches 2nd end	
Hydrostatic Test Pre	essure:
6000.0 pounds per so	juare inch
Flow Angle:	
90.0 degrees 2nd end	1
Inside Surface Cond	lition:
Smooth	
Measuring Method A	And Length:
36.000 inches workir	ıg
Thread Series Desig	nator:
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0