NSN 4720-01-043-2021

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-043-2021 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.880 inches **Minimum Inside Bending Radius:** 5.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 800.0 pounds per square inch **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 15.120 inches working **Special Features:** Layer composition and location first layer braided cotton cord or braided rayon cord, outer cover molded rubber, ethylene propylene dienne-poly-methylene **Thread Series Designator:** Unif 1st end

N/a

Shelf Life:

NSN 4720-01-043-2021

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0