Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-043-2824

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Right-hand 1st end
Inside Diameter:
0.562 inches
Tempurature Rating:
54.0 degrees celsius and 121.0 degrees celsius single response Outside Diameter:
0.797 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style: Swivel nut flare 1st end
End Connection Design:
Straight 1st end Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch Thread Size:
0.750 inches 1st end
Seat Angle: 37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
6.750 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



**Specification Data:** 

77294-41230 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0