NSN 4720-01-044-0863

Cross Sectional Shape:

Thread Direction: Right-hand 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-044-0863

Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit	it single response
Outside Diameter:	
0.937 inches	
Minimum Inside Bending Radius:	
6.000 inches	
Unable To Decode:	
Unable to decode or unable to decode	
Exterior Color:	
Black	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting steel all ends	
Fitting Component And Surface Treatment:	
Complete fitting dichromate 1st end	
Connection Type:	
Threaded external pipe 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
30000.0 pounds per square inch	
First End Swivel Action Capability:	
Not included	
Layer Composition And Location:	
1st layer braided textile yarn err-100	
Maximum Operating Pressure:	
7500.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
15000.0 pounds per square inch	

NSN 4720-01-044-0863

Nonmetallic Hose Assembly - Page 2 of 2



Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches

Special Features:

Inner conveying tube material-rubber, buna-n or chloroprene

Thread Series Designator:

Nptf 1st end

Specification Or Standard:

6 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0