Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-044-6036

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.880 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.230 inches
Minimum Inside Bending Radius:
7.380 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer spirally laid steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0