Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-045-6717

Cross Section	ал эпаре:
Thread Class	
3b 1st end	
	tion.
Thread Direct	
Right-hand 1s	
Inside Diamet	ter:
0.212 inches	
Tempurature	-
-	fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diam	leter:
0.390 inches	
	ide Bending Radius:
1.500 inches	
Connection S	
	areless 1st end
End Connecti	-
Straight 1st en	
Connection T	уре:
Threaded inter	rnal tube 1st end
Features Prov	vided:
Nuts drilled for	rlockwire
Burst Test Pr	essure:
12000.0 pound	ds per square inch
Layer Compo	sition And Location:
Outer layer bra	aided corrosion resistant steel wire
Maximum Op	erating Pressure:
3000.0 pounds	s per square inch
Thread Size:	
0.438 inches 1	st end
Hydrostatic T	est Pressure:
6000.0 pounds	s per square inch
Inside Surfac	e Condition:
Smooth	
Measuring Me	ethod And Length:
14.000 inches	working
Thread Series	s Designator:
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measu	ure:

---

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

