

View Online at <https://aerobasegroup.com/nsn/4720-01-046-3451>

Cross Sectional Shape:

Round

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 2nd end

Inside Diameter:

0.298 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.475 inches

Minimum Inside Bending Radius:

2.500 inches

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 2nd end

Features Provided:

Nuts drilled for lockwire

Burst Test Pressure:

10500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.125 inches working

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0