NSN 4720-01-046-3451

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-046-3451 **Cross Sectional Shape:** Round **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 2nd end **Inside Diameter:** 0.298 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.475 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Swivel nut, flareless 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 2nd end **Features Provided:** Nuts drilled for lockwire **Burst Test Pressure:** 10500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth

Measuring Method And Length:

21.125 inches working

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

NSN 4720-01-046-3451

Nonmetallic Hose Assembly - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0