## NSN 4720-01-046-9618

Nonmetallic Hose Assembly - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/4720-01-046-9618  |
|--|
| Cross Sectional Shape:   |
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.250 inches   |
| Outside Diameter:  |
| 0.690 inches   |
| Exterior Color:  |
| Black  |
| End Application:   |
| SELF-CO-NTA-INED   |
| Connection Style:  |
| Plain 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded external pipe 1st end   |
| Features Provided:   |
| Perforated outer cover   |
| Burst Test Pressure:   |
| 20000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, chloroprene   |
| Maximum Operating Pressure:  |
| 5000.0 pounds per square inch  |
| Thread Size:   |
| 0.125 inches 1st end   |
| Hydrostatic Test Pressure:   |
| 10000.0 pounds per square inch   |
| Outer Covering Environmental Protection:   |
| Oil resistant  |
| Criticality Code Justification:  |
| Agav   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 22.000 inches  |
| Special Features:  |
| This transports breathing air from cylinder and valve assembly, 4240-00-947-5329 to air pressure regulator, 4240-00-927-2486; see af to. |
| 14s5-11-11, fig. 8-1 and 8-4   |
| Thread Series Designator:  |

Nptf 1st end

## NSN 4720-01-046-9618

Nonmetallic Hose Assembly - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0