

View Online at <https://aerobasegroup.com/nsn/4720-01-046-9618>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Outside Diameter:**

0.690 inches

**Exterior Color:**

Black

**End Application:**

SELF-CO-NTA-INED

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Perforated outer cover

**Burst Test Pressure:**

20000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

0.125 inches 1st end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant

**Criticality Code Justification:**

Agav

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

22.000 inches

**Special Features:**

This transports breathing air from cylinder and valve assembly, 4240-00-947-5329 to air pressure regulator, 4240-00-927-2486; see af to.

14s5-11-11, fig. 8-1 and 8-4

**Thread Series Designator:**

Nptf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0