NSN 4720-01-046-9618

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4720-01-046-9618
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Outside Diameter:
0.690 inches
Exterior Color:
Black
End Application:
SELF-CO-NTA-INED
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Perforated outer cover
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.125 inches 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Criticality Code Justification:
Agav
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.000 inches
Special Features:
This transports breathing air from cylinder and valve assembly, 4240-00-947-5329 to air pressure regulator, 4240-00-927-2486; see af to.
14s5-11-11, fig. 8-1 and 8-4
Thread Series Designator:

Nptf 1st end

NSN 4720-01-046-9618

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0