Nonmetallic Hose Assembly - Page 1 of 2



molded rubber, chloroprene

View Online at https://aerobasegroup.com/nsn/4720-01-047-1152

| Cro | ss Sectional Shape: |
|-------|--|
| Rou | nd |
| Thre | ead Class: |
| 3b 1 | st end |
| Thre | ead Direction: |
| Rigł | nt-hand 1st end |
| Insi | de Diameter: |
| 0.25 | i0 inches |
| Tem | npurature Rating: |
| -65. | 0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Out | side Diameter: |
| 0.69 | 00 inches |
| Min | imum Inside Bending Radius: |
| 4.00 | 00 inches |
| Con | nection Style: |
| Swiv | vel nut flare 1st end |
| End | Connection Design: |
| Stra | ight 1st end |
| Con | nection Type: |
| Thre | eaded internal tube 1st end |
| Bur | st Test Pressure: |
| 200 | 00.0 pounds per square inch |
| Lay | er Composition And Location: |
| 1st I | ayer braided corrosion resistant steel wire and 2nd layer spirally laid steel wire and outer layer r |
| Max | imum Operating Pressure: |
| 500 | 0.0 pounds per square inch |
| Thre | ead Size: |
| 0.75 | i0 inches 1st end |
| Sea | t Angle: |
| 37.0 |) degrees 1st end |
| Hyd | rostatic Test Pressure: |
| 100 | 00.0 pounds per square inch |
| Out | er Covering Environmental Protection: |
| | ew resistant and oil resistant and oil resistant |
| Insi | de Surface Condition: |
| Smo | poth |
| Меа | suring Method And Length: |
| | 00 inches |
| | lia For Which Designed: |
| | ase and fuel/oil, hydrocarbon and water single response |
| | ead Series Designator: |
| | |

NSN 4720-01-047-1152

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

