## NSN 4720-01-048-1234

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-048-1234

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
3.375 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated cotton fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch
Outer Covering Environmental Protection:
Alcohol resistant and corrosion resistant and fuel resistant and mildew resistant and waterproof
Vacuum In Torr:
50.8

Smooth

**Inside Surface Condition:** 

## NSN 4720-01-048-1234

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
112.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0