NSN 4720-01-048-4415

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-048-4415

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.675 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 2nd end
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
Thread Size: 1.000 inches 2nd end
1.000 inches 2nd end
1.000 inches 2nd end Hydrostatic Test Pressure:
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle:
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition:
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length:
1.000 inches 2nd end Hydrostatic Test Pressure: 500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 120.000 inches working

Nh 2nd end

NSN 4720-01-048-4415

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0