NSN 4720-01-050-1336



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-050-1336 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.345 inches **Tempurature Rating:** 32.0 degrees fahrenheit and 122.0 degrees fahrenheit single response **Outside Diameter:** 0.610 inches **Minimum Inside Bending Radius:** 1.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided rayon cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 48.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unjf 1st end

Shelf Life:

N/a

NSN 4720-01-050-1336

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0