Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-050-1337

| ross Sectional Shape: |
|---|
| ound |
| hread Class: |
| b 1st end |
| hread Direction: |
| ight-hand 1st end |
| nside Diameter: |
| .512 inches |
| empurature Rating: |
| 2.0 degrees fahrenheit and 122.0 degrees fahrenheit single response |
| outside Diameter: |
| .910 inches |
| linimum Inside Bending Radius: |
| .750 inches |
| connection Style: |
| wivel nut flare 1st end |
| nd Connection Design: |
| traight 1st end |
| connection Type: |
| hreaded internal tube 1st end |
| urst Test Pressure: |
| 000.0 pounds per square inch |
| ayer Composition And Location: |
| st layer braided polyester cord and 2nd layer braided polyamide cord and outer layer braided corrosion resistant steel with |
| laximum Operating Pressure: |
| 50.0 pounds per square inch |
| hread Size: |
| .875 inches 1st end |
| eat Angle: |
| 7.0 degrees 1st end |
| ydrostatic Test Pressure: |
| 00.0 pounds per square inch |
| nside Surface Condition: |
| mooth |
| leasuring Method And Length: |
| 6.000 inches working |
| hread Series Designator: |
| njf 1st end |
| helf Life: |
| /a |
| nit Of Measure: |
| |

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

