

View Online at <https://aerobasegroup.com/nsn/4720-01-050-2524>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Mil-h-5593, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Ms27404 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

1250.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber err-100

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.500 inches working

Special Features:

Inner conveying tube material-rubber

Media For Which Designed:

Air single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-5593 spec.