

View Online at <https://aerobasegroup.com/nsn/4720-01-050-3945>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.350 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.600 inches

**Minimum Inside Bending Radius:**

5.500 inches

**Inner Conveying Tube Style:**

Annular close-pitch corrugated

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Nuts drilled for lockwire and identical ends

**Burst Test Pressure:**

5400.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1350.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

2700.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Measuring Method And Length:**

8.375 inches

**Special Features:**

Retaining wire corrosion resistant steel 321 per ams 5689 and one corrosion resistant identification band 1 in. Wide and @.012in. To .020 in.  
@thick

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0