

View Online at <https://aerobasegroup.com/nsn/4720-01-050-3946>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.350 inches

Temperature Rating:

-65.0 degrees fahrenheit and 800.0 degrees fahrenheit single response

Outside Diameter:

0.600 inches

Minimum Inside Bending Radius:

5.500 inches

Inner Conveying Tube Style:

Annular close-pitch corrugated

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Nuts drilled for lockwire and identical ends

Burst Test Pressure:

5400.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1800.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

2700.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

14.000 inches

Special Features:

Retaining wire corrosion resistant steel 321 per ams 5689 and one corrosion resistant identification band 1 in. Wide and .012 in. To .020 in. Thick

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0