## NSN 4720-01-050-7073

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-050-7073

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.670 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer braided cotton cord
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.500 inches

Media For Which Designed:

Air and ethylene glycol and fuel/oil, hydrocarbon single response

## NSN 4720-01-050-7073

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0