NSN 4720-01-051-1613

Cross Sectional Shape:

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-051-1613

| Round |
|---|
| Thread Class: |
| 2a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.343 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.546 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 331.0 |
| Quick Disconnect Size: |
| 0.875 inches 2nd end |
| End Application: |
| An/alq-155; an/alt-28 |
| Connection Style: |
| Push (internal) 2nd end |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Threaded external boss 1st end |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 50.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Hydrostatic Test Pressure: |
| 75.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 7.437 inches working |
| Thread Series Designator: |

NSN 4720-01-051-1613

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0