## NSN 4720-01-052-1519

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-052-1519

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.270 inches
Minimum Inside Bending Radius:
7.375 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyester cord and 2nd layer braided steel wire and outer layer braided polyester cord
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

Oil resistant

## NSN 4720-01-052-1519

Nonmetallic Hose Assembly - Page 2 of 2



vacuum in Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
36.000 inches working
Thread Series Designator:
Un 2nd end
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No

**Fiig:** A542a0