Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-052-5985

Cross Sectional Shape:	
Round	
Inside Diameter:	
1.000 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
1.562 inches	
Minimum Inside Bending Radius:	
12.000 inches	
Flange Outside Diameter:	
2.000 inches 2nd end	
Connection Style:	
Raised swivel w/ gasket groove 2nd end	
Raised Face Diameter:	
2.000 inches 2nd end	
End Flange Construction:	
Solid 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Raised face flange 2nd end	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic	С
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Outer Covering Environmental Protection:	
Abrasion resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.000 inches working	
Flange Style:	
Round w/ out bolt holes 2nd end	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0