Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-052-6481

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.188 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

#### **Exterior Color:**

Natural

#### **Connection Style:**

Swivel nut flare 2nd end

### End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Electrostatic discharge capability

#### **Burst Test Pressure:**

12000.0 pounds per square inch

#### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

#### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 2nd end

## Hydrostatic Test Pressure:

3000.0 pounds per square inch

#### Flow Angle:

45.0 degrees 2nd end

### **Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant

# Vacuum In Torr:

50.8

Nonmetallic Hose Assembly - Page 2 of 2



**Inside Surface Condition:** Smooth Measuring Method And Length: 49.500 inches working **Thread Series Designator:** Unjf 1st end **Specification Data:** 96906-ms8005 government standard Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0