## NSN 4720-01-053-2763

**Thread Series Designator:** 

Un 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-053-2763

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
|  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.750 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 1.250 inches   |
| Minimum Inside Bending Radius:   |
| 9.500 inches   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 12 1st end   |
| Burst Test Pressure:   |
| 9000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided cotton cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 2250.0 pounds per square inch  |
| Thread Size:   |
| 1.062 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Outer Covering Environmental Protection:   |
| Fuel resistant and oil resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 23.000 inches  |
| Media For Which Designed:  |
| Air and fuel/oil, hydrocarbon single response  |

## NSN 4720-01-053-2763

Nonmetallic Hose Assembly - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0