

View Online at <https://aerobasegroup.com/nsn/4720-01-053-2770>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

0.766 inches

Minimum Inside Bending Radius:

4.625 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Perforated outer cover

Second End Relationship With First End:

Identical

Burst Test Pressure:

8000.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Vacuum In Torr:

30.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Special Features:

Inner conveying tube material-rubber, buna-n

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0