Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-053-6577

RoundThread Class:3b 1st endThread Direction:Right-hand 1st endTempurature Rating:65.0 degrees fahrenheit and 400.0 degrees fahrenheit single responseConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:Ist layer braided corrosion resistant steel wire and outer layer braided corrosion resistant
3b 1st endThread Direction:Right-hand 1st endTempurature Rating:-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single responseConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:
Thread Direction:Right-hand 1st endTempurature Rating:-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single responseConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:
Right-hand 1st endTempurature Rating:-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single responseConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:
Tempurature Rating:-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single responseConnection Style:Swivel nut, flareless 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endLayer Composition And Location:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location:
Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location:
Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location:
End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location:
Straight 2nd end Connection Type: Threaded internal tube 1st end Layer Composition And Location:
Connection Type: Threaded internal tube 1st end Layer Composition And Location:
Threaded internal tube 1st end Layer Composition And Location:
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
17.625 inches working and 17.875 inches working
Thread Series Designator:
Unjs 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0