Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-054-6034

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.500 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 2.060 inches  |
| Minimum Inside Bending Radius:  |
| 20.000 inches   |
| Connection Style:   |
| Inverted flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external pipe 1st end  |
| Burst Test Pressure:  |
| 20000.0 pounds per square inch  |
| Layer Composition And Location:                                       |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:   |
| 500.0 pounds per square inch  |
| Thread Size:  |
| 1.500 inches 1st end  |
| Seat Angle:   |
| 30.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 1000.0 pounds per square inch   |
| Outer Covering Environmental Protection:                              |
| Mildew resistant and oil resistant and oil resistant                  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 32.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                 |
| Thread Series Designator:   |
| Nptf 1st end  |
| Shelf Life:   |
| N/a   |
|   |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0