

View Online at <https://aerobasegroup.com/nsn/4720-01-055-4026>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

16.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

2500.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

39.750 inches

Special Features:

Has global american fittings

Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0