## NSN 4720-01-055-6983

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-055-6983

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer wrapped rubber, synthetic and 3rd layer braided steel wire and outer layer wrapped rubber,
synthetic
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Hydrostatic Test Pressure:
10000.0 pounds per square inch
Outer Covering Environmental Protection:
Hydraulic solution resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
50.000 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

-

**Unit Of Measure:** 

## NSN 4720-01-055-6983

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0